

Dimensioning of Bio Filters

Prof. Dr. Werner Bidlingmaier & Dr.-Ing. Christian Springer

Projekt Orbit | Dr. W. Bidlingmaier | Bauhaus Universität Weimar | www.orbit-online.net

1 Equilibrium Concentration of harmful Gas in the Liquid of a Scrubber

Henry- respectively Dalton-Gesetz

$$C_g = H * C_L$$

C_g	Concentration of a gas component in the gas phase	[mg/m ³]
H	Absorption constant (Henry-constant)	[-]
C_L	Equilibrium Concentration	[mg/m ³]

2 Pressure Lost in the Bio Filter (per meter filter height ca. 200 Pa - 2000 Pa):

$$p_T = p_R + p_U + p_F + p_D$$

p_T	total pressure increase	[N/m ²]
p_R	pressure losses by friction in pipes	[N/m ²]
p_U	pressure losses by direction change in pipes	[N/m ²]
p_G	resistance value of aggregates (e.g. dust separator, heat exchanger, humidifier)	[N/m ²]
p_F	filter pressure lost	[N/m ²]
p_D	dynamik outlet pressure	[N/m ²]

3 Filter Load**Surface Filter****Load:**

- 1 - 20 m³/(m² * h)
- 20 - 300 m³/(m² * h)

Container filter**Load:**

- 50 - 500 m³/(m² * h)

Force Parameter:

VDI-Richtlinie 3477 named three force parameter:

- filter surface load [m³/(m² * h)],
possible load for odor deodorization ca. 30 - 200 m³/(m² * h)
- filter volume load [m³/(m³ * h)],
usual load for odor deodorization ca. 40 - 200 m³/(m³ * h)
- specific filter load [g/(m³ * h)],
odor deodorization [GE/(m³ * h)],
- usual range for the biological degradation ca. 20 - 200 g/(m³ * h)